VIVASIO

INSTALLATION GUIDE

No-drill suction hooks

Stainless steel, set of 2.



01

Clean

Remove dust, grease and cleaning residue from the surface and let it dry completely.



02

Open the hook

Turn the knob anticlockwise and separate the parts.



03

Remove the film


Peel the protective film completely off the suction cup.



04

Press on

Place the suction cup and press it firmly from the centre outwards.



05

Insert the ring

Insert the plastic ring into the stainless steel base.



06

Fit the base

Place the base with the ring onto the suction cup.



07

Tighten

Keep pressing, fit the knob and turn it clockwise until tight.



08

Wait 24 hours

Leave the hook unloaded for 24 hours. After that it holds up to 3 kg.

! IMPORTANT

Smooth, non-porous surfaces only: tiles, glass, metal, mirror.

On tiles, mount away from the grout lines.

Not suitable for rough, textured or uneven walls.

Maximum 3 kg per hook.

REMOVAL AND CARE

Loosen the knob anticlockwise and take the hook off.

Removable without residue and reusable.

If the grip weakens: wash the suction cup in warm water, let it dry and reattach it.

TECHNICAL DATA

Material	Stainless steel
Suction surface	Silicone
Suction cup	Ø 60 mm
Hook head	Ø 28 mm
Depth from wall	45 mm
Load capacity	up to 3 kg per hook